

UNCONTROLLED

HUNTAWAY PROTECTOR-COTE STRIPPER

ChemWatch Material Safety Data Sheet
Issue Date: Tue 10-Jul-2001

CHEMWATCH 4706-46
CD 2004/3 Page 1 of 12

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

HUNTAWAY PROTECTOR-COTE STRIPPER

SYNONYMS

cleaner Protector- Coat (misspelling)
CPCL- 100 Cobblestone Paving

PRODUCT USE


Cleaner to remove Huntaway Protector-Cote No.1.

SUPPLIER

Company: Cobblestone Paving Australia P/L
Address:
PO Box 2057
Burleigh Mdc, Gold Coast
QLD, 4220
AUS

Company: Cobblestone Paving Australia P/L
Address:
45 Alex Fisher Drive
Burleigh Gardens
QLD, 4220
AUS
Telephone: +61 7 5593 7766
Fax: 07 5593 7777

HAZARD RATINGS



Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS.

According to the Criteria of NOHSC, and the ADG Code.



HUNTAWAY PROTECTOR-COTE STRIPPER

ChemWatch Material Safety Data Sheet
Issue Date: Tue 10-Jul-2001

CHEMWATCH 4706-46
CD 2004/3 Page 2 of 12

Section 2 - HAZARDS IDENTIFICATION ...

POISONS SCHEDULE

S6

RISK

Harmful by inhalation, in contact with skin and if swallowed.
Irritating to eyes.
Limited evidence of a carcinogenic effect.
Cumulative effects may result following exposure*.
May be harmful to the foetus/ embryo*.
May possibly affect fertility*.
* (limited evidence)

SAFETY

Keep container in a well ventilated place.
Avoid exposure - obtain special instructions before use.
Keep container tightly closed.
Take off immediately all contaminated clothing.
In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
If you feel unwell contact Doctor or Poisons Information Centre. (Show the label if possible).

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
ethylene glycol monobutyl ether surfactants	111-76-2	10-19
biocide		1-15
water	7732-18-5	<1
		>60

NOTE: Manufacturer has supplied full ingredient information to allow CHEMWATCH assessment.

Section 4 - FIRST AID MEASURES

SWALLOWED

For advice, contact a Poisons Information Centre or a doctor.

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconsciousness
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

continued...

HUNTAWAY PROTECTOR-COTE STRIPPER

ChemWatch Material Safety Data Sheet
Issue Date: Tue 10-Jul-2001

CHEMWATCH 4706-46
CD 2004/3 Page 3 of 12

Section 4 - FIRST AID MEASURES ...

- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

Treat symptomatically.

Followed acute or short term repeated exposures to ethylene glycol monoalkyl ethers and their acetates:

- Hepatic metabolism produces ethylene glycol as a metabolite.
- Clinical presentation, following severe intoxication, resembles that of ethylene glycol exposures.
- Monitoring the urinary excretion of the alkoxyacetic acid metabolites may be a useful indication of exposure.

[Ellenhorn and Barceloux: Medical Toxicology]

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered to be a significant fire risk.
- Expansion or decomposition on heating may lead to violent rupture of

continued...

HUNTAWAY PROTECTOR-COTE STRIPPER

ChemWatch Material Safety Data Sheet
Issue Date: Tue 10-Jul-2001

CHEMWATCH 4706-46
CD 2004/3 Page 4 of 12

Section 5 - FIRE FIGHTING MEASURES ...

containers.

- Decomposes on heating and may produce toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.

Other decomposition products include carbon dioxide (CO₂)

FIRE INCOMPATIBILITY

Avoid reaction with oxidising agents

HAZCHEM

None

Personal Protective Equipment

Glasses:
Chemical goggles.

Gloves:
1.BUTYL 2.NEOPRENE 3.PVA

Respirator:
Type A Filter of sufficient capacity

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

Slippery when spilt.

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

MAJOR SPILLS

Slippery when spilt.

Minor hazard.

- Clear area of personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment as required.
- Prevent spillage from entering drains or water ways.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal.
- Wash area and prevent runoff into drains or waterways.
- If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

continued...

HUNTAWAY PROTECTOR-COTE STRIPPER

ChemWatch Material Safety Data Sheet
Issue Date: Tue 10-Jul-2001

CHEMWATCH 4706-46
CD 2004/3 Page 5 of 12

Section 6 - ACCIDENTAL RELEASE MEASURES ...

life-threatening health effects is:

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

other than mild, transient adverse effects without perceiving a clearly defined odour is:

American Industrial Hygiene Association (AIHA)

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

Avoid storage with oxidisers

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well ventilated area.
- DO NOT allow to freeze.
- Store away from incompatible materials.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

continued...

HUNTAWAY PROTECTOR-COTE STRIPPER

ChemWatch Material Safety Data Sheet
Issue Date: Tue 10-Jul-2001

CHEMWATCH 4706-46
CD 2004/3 Page 6 of 12

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

None assigned. Refer to individual constituents.

ODOUR SAFETY FACTOR (OSF)

OSF=2E2 (2-BUTOXY ETHANOL)

Exposed individuals are reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class A or B.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV-TWA for example) is being reached, even when distracted by working activities
B	26-550	As "A" for 50-90% of persons being distracted
C	1-26	As "A" for less than 50% of persons being distracted
D	0.18-1	10-50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As "D" for less than 10% of persons aware of being tested

REPRODUCTIVE HEALTH GUIDELINES

Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for reproductive no-observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level (LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits.

Ingredient	ORG	UF	Endpoint	CR	TLV Adeq
ethylene glycol mono	3.6 mg/m ³	100	D	NA	-

These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise.

CR = Cancer Risk/10000; UF = Uncertainty factor:

TLV believed to be adequate to protect reproductive health:

LOD: Limit of detection

Toxic endpoints have also been identified as:

continued...

HUNTAWAY PROTECTOR-COTE STRIPPER

ChemWatch Material Safety Data Sheet
Issue Date: Tue 10-Jul-2001

CHEMWATCH 4706-46
CD 2004/3 Page 7 of 12

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION ...

D = Developmental; R = Reproductive; TC = Transplacental carcinogen
Jankovic J., Drake F.: A Screening Method for Occupational Reproductive
American Industrial Hygiene Association Journal 57: 641-649 (1996)

INGREDIENT DATA

ETHYLENE GLYCOL MONOBUTYL ETHER:

TLV TWA: 20 ppm A3 [ACGIH]

PEL TWA: 50 ppm, 240 mg/m³ (SKIN) [OSHA Z1]

TLV TWA: 20 ppm A3

CAUTION: This substance has been classified by the ACGIH as A3 Animal Carcinogen
(at relatively high doses)

ES TWA: 25 ppm, 121 mg/m³ (skin) Under review

OES TWA: 25 ppm, 123 mg/m³ (skin)

Exposure limits with "skin" notation indicate that vapour and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

MAK value: 20 ppm, 98 mg/m³

Designated H in List of MAK values: Danger of cutaneous absorption.

Absorption of such substances through the skin can pose an incomparably larger danger of toxicity than their inhalation. To avoid health risks when handling such substances, meticulous cleaning of the skin, hair and clothing is imperative.

MAK Category II Peak Limitation: For substances with systemic effects and with a half-life in humans of less than two hours.

Allows excursions of 2 times the MAK value, for 30 minutes (on average), four times per shift.

MAK Group C: There is no reason to fear risk of damage to the developing embryo when MAK and BAT values are observed.

MAK values, and categories and groups are those recommended within the Federal Republic of Germany

Odour Threshold Value: 0.10 ppm (detection), 0.35 ppm (recognition)

IDLH Level: 700 ppm

Although rats appear to be more susceptible than other animals anaemia is not uncommon amongst humans following exposure. The TLV reflects the need to maintain exposures below levels found to cause blood changes in experimental animals. It is concluded that this limit will reduce the significant risk of irritation, haematologic effects and other systemic effects observed in humans and animals exposed to higher vapour concentrations. The toxic effects typical of some other glycol ethers (pancytopenia, testis atrophy and teratogenic effects) are not found with this substance.

WATER:

No exposure limits set by NOHSC or ACGIH

PERSONAL PROTECTION



continued...

HUNTAWAY PROTECTOR-COTE STRIPPER

ChemWatch Material Safety Data Sheet
Issue Date: Tue 10-Jul-2001

CHEMWATCH 4706-46
CD 2004/3 Page 8 of 12

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION ...

EYE

- Safety glasses with side shields; or as required,
- Chemical goggles.
- Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them.

HANDS/FEET

- Barrier cream and Rubber Gloves or PVC gloves

OTHER

- Overalls.
- Eyewash unit.

ENGINEERING CONTROLS

Use in a well-ventilated area.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the

continued...

HUNTAWAY PROTECTOR-COTE STRIPPER

ChemWatch Material Safety Data Sheet
Issue Date: Tue 10-Jul-2001

CHEMWATCH 4706-46
CD 2004/3 Page 9 of 12

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION ...

air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear amber liquid; mixes with water.

PHYSICAL PROPERTIES

Liquid.
Mixes with water.

Molecular Weight: Not applicable
Melting Range (°C): Not available
Solubility in water (g/L): Miscible
pH (1% solution): Not available
Volatile Component (%vol): Not available
Relative Vapour Density (air=1): Not available
Lower Explosive Limit (%): Not applicable
Autoignition Temp (°C): Not applicable
State: Liquid

Boiling Range (°C): Not available
Specific Gravity (water=1): >1
pH (as supplied): Not available
Vapour Pressure (kPa): Not available
Evaporation Rate: Not available
Flash Point (°C): Not applicable
Upper Explosive Limit (%): Not applicable
Decomposition Temp (°C): Not available

log Kow (Prager 1995): 0.83
log Kow (Sangster 1997): 0.8
log Kow: 0.76-0.83

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS SWALLOWED

Considered an unlikely route of entry in commercial/industrial environments. The liquid is discomforting to the gastro-intestinal tract and is harmful if swallowed.
Ingestion may result in nausea, abdominal irritation, pain and vomiting

continued...

HUNTAWAY PROTECTOR-COTE STRIPPER

ChemWatch Material Safety Data Sheet
Issue Date: Tue 10-Jul-2001

CHEMWATCH 4706-46
CD 2004/3 Page 10 of 12

Section 11 - TOXICOLOGICAL INFORMATION ...

EYE

The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye inflammation, ulceration.
The vapour is discomforting to the eyes.
The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

SKIN

The liquid is discomforting to the skin and may cause drying of the skin, which may lead to dermatitis.
Toxic effects may result from skin absorption.
Bare unprotected skin should not be exposed to this material.
The material may accentuate any pre-existing skin condition

INHALED

The vapour is discomforting to the upper respiratory tract and harmful if inhaled. Inhalation hazard is increased at higher temperatures.

CHRONIC HEALTH EFFECTS

Principal routes of exposure are usually by eye contact and skin contact. Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following. As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

Huntaway Protector-Cote Stripper

Not available. Refer to individual constituents.
unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances

ETHYLENE GLYCOL MONOBUTYL ETHER: TOXICITY

Oral (rat) LD50: 470 mg/kg

Dermal (rabbit) LD50: 220 mg/kg

Inhalation (human) TClO: 100 ppm

Inhalation (human) TClO: 195 ppm/8h

Inhalation (rat-male) LC50: 486 ppm *

Inhalation (rat-female) LC50: 450 ppm *

NOTE: Changes in kidney, liver, spleen and lungs are observed in animals

exposed to high concentrations of this substance by all routes.

IRRITATION

Skin (rabbit): 500 mg, open; mild

Eye (rabbit): 100 mg/24h-moderate

Eye (rabbit): 100 mg SEVERE

* [Union Carbide]

WATER:

No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

No data for Huntaway Protector-Cote Stripper.
Refer to data for ingredients, which follows:

ETHYLENE GLYCOL MONOBUTYL ETHER:
Hazardous Air Pollutant: No
Fish LC50 (96hr.) (mg/l): 1490
BCF<100: 0.4
log Kow (Prager 1995): 0.83

continued...

HUNTAWAY PROTECTOR-COTE STRIPPER

ChemWatch Material Safety Data Sheet
Issue Date: Tue 10-Jul-2001

CHEMWATCH 4706-46
CD 2004/3 Page 11 of 12

Section 12 - ECOLOGICAL INFORMATION ...

log Kow (Sangster 1997): 0.8
Half-life Soil - High (hours): 672
Half-life Soil - Low (hours): 168
Half-life Air - High (hours): 32.8
Half-life Air - Low (hours): 3.28
Half-life Surface water - High (hours): 672
Half-life Surface water - Low (hours): 168
Half-life Ground water - High (hours): 1344
Half-life Ground water - Low (hours): 336
Aqueous biodegradation - Aerobic - High (hours): 672
Aqueous biodegradation - Aerobic - Low (hours): 168
Aqueous biodegradation - Anaerobic - High (hours): 2688
Aqueous biodegradation - Anaerobic - Low (hours): 672
Photooxidation half-life air - High (hours): 32.8
Photooxidation half-life air - Low (hours): 3.28
Hazardous Air Pollutant: No
Fish LC50 (96hr.) (mg/l): 1250-1650
Daphnia magna EC50 (48hr.) (mg/l): 600-1000

log Kow: 0.76-0.83
Koc: 67
Half-life (hr) air: 17
Henry's atm m3 /mol: 2.08E-08
BOD 5 if unstated: 0.71
COD: 2.2
Log BCF: 0.4
Fish toxicity:
(-) 24h LD50: 983-1650 mg/L
(Fathead minnow) 96h LC50: 1700 mg/L **
Invertebrate toxicity:
cell mult. inhib.91-900mg/L
(Daphnia) 48h LC50: >1000 mg/L **
Bioaccumulation: not sig
Effects on algae and plankton: cell mult. inhib.35-900mg/L
Degradation Biological: rapid
processes Abiotic: no hydrol&photonol,RxnOH*

** [Union Carbide]

WATER:

No data for water.

Section 13 - DISPOSAL CONSIDERATIONS

- Consult manufacturer for recycling options and recycle where possible .
- Consult State Land Waste Management Authority for disposal.
- Incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

Shipping Name:
NONE
Dangerous Goods Class: None
UN/NA Number: None
ADR Number:

continued...

HUNTAWAY PROTECTOR-COTE STRIPPER

ChemWatch Material Safety Data Sheet

Issue Date: Tue 10-Jul-2001

CHEMWATCH 4706-46

CD 2004/3 Page 12 of 12

Section 14 - TRANSPORTATION INFORMATION ...

Packing Group: None

Labels Required:

Additional Shipping Information:

International Transport Regulations:

IMO: None

HAZCHEM

None

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE

S6

REGULATIONS

No data available for water (CAS: 7732-18-5).

Section 16 - OTHER INFORMATION

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Tue 10-Jul-2001

Print Date: Mon 16-Aug-2004