

# UNCONTROLLED

## LUSTRESEAL WATER & OIL REPELLENT

ChemWatch Material Safety Data Sheet  
Issue Date: Thu 6-Nov-2003

CHEMWATCH 4714-37  
CD 2004/3 Page 1 of 8

### Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

#### PRODUCT NAME

LUSTRESEAL WATER & OIL REPELLENT

#### SYNONYMS

Cobblestone Paving

#### PRODUCT USE


Water and oil repellent coating.

#### SUPPLIER

Company: Cobblestone Paving Australia P/L  
Address:  
PO Box 2057  
Burleigh Mdc, Gold Coast  
QLD, 4220  
AUS

Company: Cobblestone Paving Australia P/L  
Address:  
45 Alex Fisher Drive  
Burleigh Gardens  
QLD, 4220  
AUS  
Telephone: +61 7 5593 7766  
Fax: 07 5593 7777

#### HAZARD RATINGS



### Section 2 - HAZARDS IDENTIFICATION

#### STATEMENT OF HAZARDOUS NATURE

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS.

According to the Criteria of NOHSC, and the ADG Code.

#### POISONS SCHEDULE

None

#### RISK

#### SAFETY

continued...

# LUSTRESEAL WATER & OIL REPELLENT

ChemWatch Material Safety Data Sheet  
Issue Date: Thu 6-Nov-2003

CHEMWATCH 4714-37  
CD 2004/3 Page 2 of 8

---

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

---

NAME	CAS RN	%
resin, unregulated bacteriacide		5-20 <1

NOTE: Manufacturer has supplied full ingredient information to allow CHEMWATCH assessment.

---

## Section 4 - FIRST AID MEASURES

---

### SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

### EYE

If this product comes in contact with eyes:

- Wash out immediately with water.
- If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

### INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

### NOTES TO PHYSICIAN

Treat symptomatically.

---

## Section 5 - FIRE FIGHTING MEASURES

---

### EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area

### FIRE FIGHTING

- Use water delivered as a fine spray to control fire and cool adjacent area.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

### FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered a significant fire risk, however containers may burn.

### FIRE INCOMPATIBILITY

None known.

continued...

# LUSTRESEAL WATER & OIL REPELLENT

ChemWatch Material Safety Data Sheet  
Issue Date: Thu 6-Nov-2003

CHEMWATCH 4714-37  
CD 2004/3 Page 3 of 8

---

## Section 5 - FIRE FIGHTING MEASURES ...

---

### HAZCHEM

None

### Personal Protective Equipment

Glasses:  
Chemical goggles.

Gloves:  
When handling larger quantities:  
General purpose rubber glove.

Respirator:

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

### EMERGENCY PROCEDURES

#### MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

#### MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment.
- Prevent spillage from entering drains, sewers or water courses.
- Recover product wherever possible.
- Put residues in labelled containers for disposal.
- If contamination of drains or waterways occurs, advise emergency services.

### EMERGENCY RESPONSE PLANNING GUIDLINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

other than mild, transient adverse effects without perceiving a clearly defined odour is:

American Industrial Hygiene Association (AIHA)

**Personal Protective Equipment advice is contained in Section 8 of the MSDS.**

continued...

# LUSTRESEAL WATER & OIL REPELLENT

ChemWatch Material Safety Data Sheet  
Issue Date: Thu 6-Nov-2003

CHEMWATCH 4714-37  
CD 2004/3 Page 4 of 8

---

## Section 7 - HANDLING AND STORAGE

---

### PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

### SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer
- Check all containers are clearly labelled and free from leaks.

### STORAGE INCOMPATIBILITY

Avoid contamination of water, foodstuffs, feed or seed.  
None known

### STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

---

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### EXPOSURE CONTROLS

Not available. Refer to individual constituents.

### PERSONAL PROTECTION

#### EYE

- Safety glasses with side shields
- Chemical goggles.

continued...

# LUSTRESEAL WATER & OIL REPELLENT

ChemWatch Material Safety Data Sheet  
Issue Date: Thu 6-Nov-2003

CHEMWATCH 4714-37  
CD 2004/3 Page 5 of 8

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION ...

- Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them.

### HANDS/FEET

Wear general protective gloves, eg. light weight rubber gloves.

### OTHER

No special equipment needed when handling small quantities.

#### OTHERWISE:

- Overalls.
- Barrier cream.
- Eyewash unit.

## ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

#### Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

#### Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after

continued...

# LUSTRESEAL WATER & OIL REPELLENT

ChemWatch Material Safety Data Sheet  
Issue Date: Thu 6-Nov-2003

CHEMWATCH 4714-37  
CD 2004/3 Page 6 of 8

---

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION ...

---

reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

---

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

---

### APPEARANCE

Liquid; mixes with water.

### PHYSICAL PROPERTIES

Liquid.  
Mixes with water.

Molecular Weight: Not Applicable  
Melting Range (°C): Not Available  
Solubility in water (g/L): Miscible  
pH (1% solution): Not Available  
Volatile Component (%vol): Not Available  
Relative Vapour Density (air=1): Not Available  
Lower Explosive Limit (%): Not Applicable  
Autoignition Temp (°C): Not Available  
State: Liquid

Boiling Range (°C): Not Available  
Specific Gravity (water=1): Not Available  
pH (as supplied): Not Available  
Vapour Pressure (kPa): Not Available  
Evaporation Rate: Not Available  
Flash Point (°C): Not Applicable  
Upper Explosive Limit (%): Not Applicable  
Decomposition Temp (°C): Not Available

---

## Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

---

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

---

## Section 11 - TOXICOLOGICAL INFORMATION

---

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS SWALLOWED

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

continued...

# LUSTRESEAL WATER & OIL REPELLENT

ChemWatch Material Safety Data Sheet  
Issue Date: Thu 6-Nov-2003

CHEMWATCH 4714-37  
CD 2004/3 Page 7 of 8

---

## Section 11 - TOXICOLOGICAL INFORMATION ...

---

### EYE

Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

### SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

### INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

### CHRONIC HEALTH EFFECTS

Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

## Lustre Seal Water & Oil Repellent

None assigned. Refer to individual constituents.  
unless otherwise specified data extracted from RTECS - Register of Toxic Effects  
of Chemical Substances

---

## Section 12 - ECOLOGICAL INFORMATION

---

No data for Lustre Seal Water & Oil Repellent.

---

## Section 13 - DISPOSAL CONSIDERATIONS

---

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material)
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

---

## Section 14 - TRANSPORTATION INFORMATION

---

Shipping Name:  
None  
Dangerous Goods Class: None  
UN/NA Number: None  
ADR Number:  
Packing Group: None  
Labels Required:  
Additional Shipping Information:

continued...

# LUSTRESEAL WATER & OIL REPELLENT

ChemWatch Material Safety Data Sheet

Issue Date: Thu 6-Nov-2003

CHEMWATCH 4714-37

CD 2004/3 Page 8 of 8

---

## Section 14 - TRANSPORTATION INFORMATION ...

---

International Transport Regulations:

IMO: None

## HAZCHEM

None

---

## Section 15 - REGULATORY INFORMATION

---

## POISONS SCHEDULE

None

## REGULATIONS

---

## Section 16 - OTHER INFORMATION

---

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Thu 6-Nov-2003

Print Date: Mon 16-Aug-2004