

LUSTRESEAL WATER BASED SEALER

ChemWatch Material Safety Data Sheet
Issue Date: Thu 1-Aug-2002

CHEMWATCH 4921-79
CD 2004/3 Page 2 of 9

Section 2 - HAZARDS IDENTIFICATION ...

SAFETY

Wear eye/face protection.
In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
acrylate/methacrylate copolymer		10-30
nonhazardous ingredients including, water	7732-18-5	>60

NOTE: Manufacturer has supplied full ingredient information to allow CHEMWATCH assessment.

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

Treat symptomatically.

continued...

LUSTRESEAL WATER BASED SEALER

ChemWatch Material Safety Data Sheet
Issue Date: Thu 1-Aug-2002

CHEMWATCH 4921-79
CD 2004/3 Page 3 of 9

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- The material is not readily combustible under normal conditions.
 - However, it will break down under fire conditions and the organic component may burn.
 - Not considered to be a significant fire risk.
 - Heat may cause expansion or decomposition with violent rupture of containers.
 - Decomposes on heating and may produce toxic fumes of carbon monoxide (CO).
 - May emit acrid smoke.
- Other decomposition products include carbon dioxide (CO₂) and acrylic monomer

FIRE INCOMPATIBILITY

Avoid contamination with strong oxidising agents as ignition may result

HAZCHEM

None

Personal Protective Equipment

Glasses:
Chemical goggles.

Gloves:
PVC chemical resistant type.
Nitrile.
Neoprene.

Respirator:

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

continued...

LUSTRESEAL WATER BASED SEALER

ChemWatch Material Safety Data Sheet
Issue Date: Thu 1-Aug-2002

CHEMWATCH 4921-79
CD 2004/3 Page 4 of 9

Section 6 - ACCIDENTAL RELEASE MEASURES ...

MAJOR SPILLS

Minor hazard.

- Clear area of personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment as required.
- Prevent spillage from entering drains or water ways.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal.
- Wash area and prevent runoff into drains or waterways.
- If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

other than mild, transient adverse effects without perceiving a clearly defined odour is:

American Industrial Hygiene Association (AIHA)

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Lined metal can, Lined metal pail/ can
- Plastic pail
- Polyliner drum
- Packing as recommended by manufacturer.

continued...

LUSTRESEAL WATER BASED SEALER

ChemWatch Material Safety Data Sheet
Issue Date: Thu 1-Aug-2002

CHEMWATCH 4921-79
CD 2004/3 Page 5 of 9

Section 7 - HANDLING AND STORAGE ...

- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

Avoid storage with oxidisers

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well ventilated area.
- DO NOT allow to freeze.
- Store away from incompatible materials.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

None assigned.

WATER:

No exposure limits set by NOHSC or ACGIH

PERSONAL PROTECTION

EYE

- Safety glasses with side shields; or as required,
- Chemical goggles.
- Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them.

HANDS/FEET

- Barrier cream and Neoprene gloves or Nitrile gloves or Wear chemical protective gloves, eg. PVC. Wear safety footwear.

OTHER

- Overalls.
- Eyewash unit.

ENGINEERING CONTROLS

Use in a well-ventilated area.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh

continued...

LUSTRESEAL WATER BASED SEALER

ChemWatch Material Safety Data Sheet
Issue Date: Thu 1-Aug-2002

CHEMWATCH 4921-79
CD 2004/3 Page 6 of 9

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION ...

circulating air required to effectively remove the contaminant.

Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank (in still air)	Air Speed: 0.25-0.5 m/s (50-100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Milky white emulsion with a slight acrylic odour; mixes with water.

PHYSICAL PROPERTIES

Liquid.
Mixes with water.

continued...

LUSTRESEAL WATER BASED SEALER

ChemWatch Material Safety Data Sheet
Issue Date: Thu 1-Aug-2002

CHEMWATCH 4921-79
CD 2004/3 Page 7 of 9

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES ...

Molecular Weight: Not applicable
Melting Range (°C): Not available
Solubility in water (g/L): Miscible
pH (1% solution): Not available
Volatile Component (%vol): Not available
Relative Vapour Density (air=1): Not available
Lower Explosive Limit (%): Not applicable
Autoignition Temp (°C): Not available
State: Liquid

Boiling Range (°C): Not available
Specific Gravity (water=1): Not available
pH (as supplied): Not available
Vapour Pressure (kPa): Not available
Evaporation Rate: Not available
Flash Point (°C): Not applicable
Upper Explosive Limit (%): Not applicable
Decomposition Temp (°C): Not available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Considered an unlikely route of entry in commercial/industrial environments. The liquid is discomforting and may be harmful if swallowed in large quantity. Ingestion may result in nausea, abdominal irritation, pain and vomiting

EYE

The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye inflammation, ulceration

SKIN

The liquid is mildly discomforting and adhesive to the skin and is capable of causing skin reactions which may lead to dermatitis

INHALED

The vapour/mist is discomforting to the upper respiratory tract and lungs. Acrylic polymer emulsions may contain residual traces of odourous acrylic monomers; the amounts remaining in compounded mixtures represents a very low order of exposure, however this may become noticeable with some materials particularly in confined or poorly ventilated spaces.

CHRONIC HEALTH EFFECTS

Principal routes of exposure are by accidental skin and eye contact and by inhalation of vapours especially at higher temperatures. Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following. As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

Lustre Seal Water Based Sealer

Not available.

continued...

LUSTRESEAL WATER BASED SEALER

ChemWatch Material Safety Data Sheet
Issue Date: Thu 1-Aug-2002

CHEMWATCH 4921-79
CD 2004/3 Page 8 of 9

Section 11 - TOXICOLOGICAL INFORMATION ...

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances

WATER:

No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

No data for Lustre Seal Water Based Sealer.
Refer to data for ingredients, which follows:

WATER:

No data for water.

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

Shipping Name:

NONE

Dangerous Goods Class: None

UN/NA Number: None

ADR Number:

Packing Group: None

Labels Required:

Additional Shipping Information:

International Transport Regulations:

IMO: None

HAZCHEM

None

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE

None

REGULATIONS

No data available for water (CAS: 7732-18-5).

continued...

LUSTRESEAL WATER BASED SEALER

ChemWatch Material Safety Data Sheet
Issue Date: Thu 1-Aug-2002

CHEMWATCH 4921-79
CD 2004/3 Page 9 of 9

Section 16 - OTHER INFORMATION

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Thu 1-Aug-2002
Print Date: Mon 16-Aug-2004