

UNCONTROLLED

MASTERSHIELD DECORATIVE GLITTER

ChemWatch Material Safety Data Sheet
Issue Date: Fri 12-Oct-2001

CHEMWATCH 4604-29
CD 2004/3 Page 1 of 9

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

MASTERSHIELD DECORATIVE GLITTER

SYNONYMS

Cobblestone Paving

PRODUCT USE


For decoration in Mastershield Polymer Flooring.

SUPPLIER

Company: Cobblestone Paving Australia P/L
Address:
PO Box 2057
Burleigh Mdc, Gold Coast
QLD, 4220
AUS

Company: Cobblestone Paving Australia P/L
Address:
45 Alex Fisher Drive
Burleigh Gardens
QLD, 4220
AUS
Telephone: +61 7 5593 7766
Fax: 07 5593 7777

HAZARD RATINGS



Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS.

According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

None

RISK

SAFETY

continued...

MASTERSHIELD DECORATIVE GLITTER

ChemWatch Material Safety Data Sheet
Issue Date: Fri 12-Oct-2001

CHEMWATCH 4604-29
CD 2004/3 Page 2 of 9

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
polyethylene terephthalate	9003-68-3	>60
coated aluminium metallized additives		

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If dust is inhaled, remove from contaminated area.
- Encourage patient to blow nose to ensure clear passage of breathing.
- If irritation or discomfort persists seek medical attention.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Use water delivered as a fine spray to control fire and cool adjacent area.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Solid which exhibits difficult combustion or is difficult to ignite.
- Avoid generating dust, particularly clouds of dust in a confined or

continued...

MASTERSHIELD DECORATIVE GLITTER

ChemWatch Material Safety Data Sheet

Issue Date: Fri 12-Oct-2001

CHEMWATCH 4604-29

CD 2004/3 Page 3 of 9

Section 5 - FIRE FIGHTING MEASURES ...

unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited

- Dry dust can also be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport.
- Build-up of electrostatic charge may be prevented by bonding and grounding.
- Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.

FIRE INCOMPATIBILITY

Avoid contamination with strong oxidising agents as ignition may result

HAZCHEM

None

Personal Protective Equipment

Glasses:
Safety Glasses.

Gloves:
General purpose rubber glove.

Respirator:
Particulate

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Wear impervious gloves and safety glasses.
- Use dry clean up procedures and avoid generating dust.
- Sweep up or
- Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).
- Place spilled material in clean, dry, sealable, labelled container.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment and dust respirator.
- Prevent spillage from entering drains, sewers or water courses.
- Avoid generating dust.
- Sweep, shovel up. Recover product wherever possible.
- Put residues in labelled plastic bags or other containers for disposal.
- If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDLINES (ERPG)

continued...

MASTERSHIELD DECORATIVE GLITTER

ChemWatch Material Safety Data Sheet
Issue Date: Fri 12-Oct-2001

CHEMWATCH 4604-29
CD 2004/3 Page 4 of 9

Section 6 - ACCIDENTAL RELEASE MEASURES ...

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

other than mild, transient adverse effects without perceiving a clearly defined odour is:

American Industrial Hygiene Association (AIHA)

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- When handling DO NOT eat, drink or smoke.
- Always wash hands with soap and water after handling.
- Avoid physical damage to containers.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.

SUITABLE CONTAINER

Packaging as recommended by manufacturer.

STORAGE INCOMPATIBILITY

Avoid storage with oxidisers

STORAGE REQUIREMENTS

- Keep dry.
- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials.
- Protect containers against physical damage.
- Check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

None assigned. Refer to individual constituents.

continued...

MASTERSHIELD DECORATIVE GLITTER

ChemWatch Material Safety Data Sheet
Issue Date: Fri 12-Oct-2001

CHEMWATCH 4604-29
CD 2004/3 Page 5 of 9

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION ...

EXPOSURE STANDARDS FOR MIXTURE

"Worst Case" computer-aided prediction of spray/ mist or fume/ dust components and concentration:

Composite Exposure Standard for Mixture (TWA) :3 mg/m³.

Operations which produce a spray/mist or fume/dust, introduce particulates to the breathing zone.

If the breathing zone concentration of ANY of the components listed below is exceeded, "Worst Case" considerations deem the individual to be overexposed.

Component Breathing Zone ppm Breathing Zone mg/m³ Mixture Conc (%)

Component	Breathing Zone (mg/m ³)	Mixture Conc (%)
polyethylene terephthalate	3.0000	100.0

INGREDIENT DATA

POLYETHYLENE TEREPHTHALATE:

TLV TWA: 10 mg/m³ (Value for particulate matter containing no asbestos and <1% crystalline silica, Inhalable fraction) [ACGIH]

TLV TWA: 3 mg/m³ (Value for particulate matter containing no asbestos and <1% crystalline silica, Respirable fraction) [ACGIH]

Dusts not otherwise classified, as inspirable dust;

ES TWA: 10 mg/m³.

Particulate (insoluble or poorly soluble *) Not Otherwise Specified (P.N.O.C)

TLV TWA: 10 mg/m³ Inhalable particulate

TLV TWA: 3 mg/m³ Respirable particulate

OEL-Sweden, United Kingdom: 10 mg/m³ total dust, 5 mg/m³ respirable dust

These "dusts" have little adverse effect on the lungs and do not produce toxic effects or organic disease. Although there is no dust which does not evoke some cellular response at sufficiently high concentrations, the cellular response caused by P.N.O.C.s has the following characteristics:

- the architecture of the air spaces remain intact,
- scar tissue (collagen) is not synthesised to any degree,
- tissue reaction is potentially reversible.

Extensive concentrations of P.N.O.C.s may:

- seriously reduce visibility,
- cause unpleasant deposits in the eyes, ears and nasal passages,
- contribute to skin or mucous membrane injury by chemical or mechanical action, per se, or by the rigorous skin cleansing procedures necessary for their removal. [ACGIH]

This limit does not apply:

- to brief exposures to higher concentrations
- nor does it apply to those substances that may cause physiological impairment at lower concentrations but for which a TLV has as yet to be determined.

This exposure standard applies to particles which

- are insoluble or poorly soluble* in water or, preferably, in aqueous lung fluid (if data is available) and
- have a low toxicity (i.e.. are not cytotoxic, genotoxic, or otherwise chemically reactive with lung tissue, and do not emit ionizing radiation, cause immune sensitization, or cause toxic effects other than by inflammation or by a mechanism of lung overload)

* Notice of intended change

continued...

MASTERSHIELD DECORATIVE GLITTER

ChemWatch Material Safety Data Sheet
Issue Date: Fri 12-Oct-2001

CHEMWATCH 4604-29
CD 2004/3 Page 6 of 9

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION ...

PERSONAL PROTECTION



EYE

- Safety glasses.
- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them.

HANDS/FEET

Wear general protective gloves, eg. light weight rubber gloves.

OTHER

- Overalls.
- Impervious protective clothing.
- Eyewash unit.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank (in still air)	Air Speed: 0.25-0.5 m/s (50-100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

Upper end of the range

continued...

MASTERSHIELD DECORATIVE GLITTER

ChemWatch Material Safety Data Sheet
Issue Date: Fri 12-Oct-2001

CHEMWATCH 4604-29
CD 2004/3 Page 7 of 9

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION ...

1: Room air currents minimal or favourable to capture
2: Contaminants of low toxicity or of nuisance value only
3: Intermittent, low production.
4: Large hood or large air mass in motion

1: Disturbing room air currents
2: Contaminants of high toxicity
3: High production, heavy use
4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Small coloured flakes; does not mix with water.

PHYSICAL PROPERTIES

Solid.
Does not mix with water.

Molecular Weight: Not applicable
Melting Range (°C): Not available
Solubility in water (g/L): Immiscible
pH (1% solution): Not applicable
Volatile Component (%vol): 0.8
Relative Vapour Density (air=1): >1
Lower Explosive Limit (%): Not available
Autoignition Temp (°C): 497
State: Divided solid

Boiling Range (°C): Not available
Specific Gravity (water=1): Not available
pH (as supplied): Not applicable
Vapour Pressure (kPa): Negligible
Evaporation Rate: Not available
Flash Point (°C): Not available
Upper Explosive Limit (%): Not available.
Decomposition Temp (°C): Not available.

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

continued...

MASTERSHIELD DECORATIVE GLITTER

ChemWatch Material Safety Data Sheet
Issue Date: Fri 12-Oct-2001

CHEMWATCH 4604-29
CD 2004/3 Page 8 of 9

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Considered an unlikely route of entry in commercial/industrial environments.
The material is moderately discomforting to the gastro-intestinal tract and may be harmful if swallowed in large quantity

EYE

The material is moderately discomforting to the eyes and is capable of causing a mild, temporary redness of the conjunctiva (similar to wind-burn), temporary impairment of vision and/ or other transient eye damage/ ulceration

SKIN

The material may be mildly discomforting to the skin.
Open cuts, abraded or irritated skin should not be exposed to this material The material may accentuate any pre-existing skin condition

INHALED

The material is discomforting to the upper respiratory tract.
Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

CHRONIC HEALTH EFFECTS

Principal routes of exposure are usually by skin contact and inhalation. As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

Mastershield Decorative Glitter

Not available. Refer to individual constituents.
unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances

POLYETHYLENE TEREPHTHALATE:

No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

No data for Mastershield Decorative Glitter.
Refer to data for ingredients, which follows:

POLYETHYLENE TEREPHTHALATE:

No data for polyethylene terephthalate.

Section 13 - DISPOSAL CONSIDERATIONS

- Consult manufacturer for recycling options and recycle where possible .
- Consult State Land Waste Management Authority for disposal.
- Incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

continued...

MASTERSHIELD DECORATIVE GLITTER

ChemWatch Material Safety Data Sheet

Issue Date: Fri 12-Oct-2001

CHEMWATCH 4604-29

CD 2004/3 Page 9 of 9

Section 13 - DISPOSAL CONSIDERATIONS ...

Section 14 - TRANSPORTATION INFORMATION

Shipping Name:

NONE

Dangerous Goods Class: None

UN/NA Number: None

ADR Number:

Packing Group: None

Labels Required:

Additional Shipping Information:

International Transport Regulations:

IMO: None

HAZCHEM

None

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE

None

REGULATIONS

No data available for polyethylene terephthalate (CAS: 9003-68-3).

Section 16 - OTHER INFORMATION

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Fri 12-Oct-2001

Print Date: Mon 16-Aug-2004