

Safety Data Sheet

according to 91/155/EEC and ISO 11014-1

(see instructions in Annex to 93/112/EC)

Date of printing: 20.02.2003

Page: 1/7

Revised: 20.02.2003

SDS No.: 090D

HAZARDOUS ACCORDING TO THE CRITERIA OF WORKSAFE AUSTRALIA

1. Identification of the substance/preparation and company

Product

Product name

Sikafloor®-91 Part A

Manufacturer/supplier information

Manufacturer/supplier:

Sika Australia Pty Ltd

Street/postbox:

55 Elizabeth Street

Town/City and Post Code:

WETHERILL PARK NSW

Country:

Australia

Phone:

(02) 9725 1145

Telefax:

(02) 9725 3330

Emergency information phone:

1800 033 111

2. Composition/information on ingredients

Chemical characterization

Modified epoxy resin

Hazardous ingredients

Designation according to 67/548/EEC

CAS No. Concentration Danger symbols R phrases

· reaction product: bisphenol A-(epichlorhydrin)

epoxy resin (number average molecular weight \leq 700)

25068-38-6 > 60 % Xi,N 36/38,43,51/53

· oxirane, mono[(C12-14-alkyloxy)methyl]derivs.

68609-97-2 1 - 10 % Xi,N 38,43,51/53

3. Hazards identification

Hazards identification

Xi Irritant

N Dangerous to environment

Information on hazards to man and to the environment

36/38 Irritating to eyes and skin.

43 May cause sensitization by skin contact.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

* 4. First-aid measures

General instructions

In any case show the physician the Safety Data Sheet

* 4. First-aid measures (continued)

After inhalation

Ensure supply of fresh air.

In the event of symptoms take medical treatment.

After skin contact

Remove soiled or soaked clothing immediately, do not allow to dry.

In case of contact with skin wash off immediately with soap and water

Consult a doctor if skin irritation persists.

After eye contact

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water.

Seek immediate medical assistance.

After ingestion

Do not induce vomiting. Rinse mouth with water. Give a glass of water.

Summon a doctor immediately.

5. Fire-fighting measures

Suitable extinguishing media

foam

dry powder

carbon dioxide

water mist

Unsuitable extinguishing media for safety reasons

Full water jet

Exposure hazard arising from the product, its combustion products or resulting gases

In the event of fire the following can be released:

Carbon monoxide (CO)

Carbondioxide (CO₂)

Special protective equipment for fire-fighting

Use breathing apparatus.

Additional information

Cool containers with water spray jet.

Fire residues and contaminated firefighting medium must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

6. Accidental release measures

Personal precautions

- Ensure adequate ventilation.
- Use personal protective clothing.
- Use breathing apparatus if exposed to vapours/dust/aerosol.

Environmental precautions

- In case of entry into waterways, soil or drains, inform the responsible authorities.

Procedures for cleaning up

- Pick up with absorbent material.
- Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder).
- When picked up, treat material as prescribed under heading "Disposal".
- Remove residues with small amount of alcohol-based solvent.

7. Handling and storage

Handling

- Instructions for safe handling
- See chapter 8 / Personal protective equipment.

- Instructions for fire and explosion protection
- Keep away from sources of ignition - no smoking.

Storage

- Requirements for storage rooms and containers
- Keep container tightly closed in a cool, well-ventilated place.

- Combined storage instructions
- Keep away from food, beverages and animal feedstocks.

- Additional information regarding storage
- Protect from frost.
- Protect from heat and direct sunlight.
- Protect from atmospheric moisture and water.

*** 8. Exposure controls/personal protection**

Exposure Standards

25068-38-6	None established	Worksafe
68609-97-2	None established	Worksafe
106-89-8	TWA: 2 ppm (similar or equal to: 7.6 mg/m ³)	Worksafe

Personal protective equipment

- General protective and hygiene measures
- Do not inhale vapours
- Avoid contact with eyes and skin
- Take care for sufficient ventilation or exhaust on the workshop place.
- Do not eat, drink or smoke during work time.

Product name: **Sikafloor®-91 Part A**

Date of printing: 20.02.2003

Page: 4/7

Revised: 20.02.2003

SDS No.: 090D

* 8. Exposure controls/personal protection (continued)

Wash hands before breaks and after work.
Use barrier skin cream.
Remove soiled or soaked clothing immediately.

Respiratory protection
In case of insufficient ventilation.

Ori-nasal mask suitable for organic vapours.
Class of vapour filter is depending on
pollutant concentration on the scene.

Hand protection
Nitrile rubber gloves

Eye protection
Tightly fitting safety glasses

Body protection
protective clothing

9. Physical and chemical properties

Appearance

Physical state: liquid
Colour: colourless
Odour: characteristic

Data relevant to safety

	Method
Flash point	Not applicable
Density at 20°C	1.14 g/cm ³
Solubility in water at 20°C	insoluble
pH value at 20°C	6.8
Viscosity at 20°C	850 mPas

10. Stability and reactivity

Conditions to avoid

Not any known.

Materials to avoid/dangerous reactions

Hazardous reactions possible with:

Amines
Phenols
Acids
Alkalis

Thermal decomposition and hazardous decomposition products

No decomposition if used as prescribed.

*** 11. Toxicological information**

Sensitization

When skin contact:

Sensitization/allergic reaction possible.

Allergic reaction can may be observed in sensitized persons, even on very low concentrations.

Experience on humans

When skin contact:

Irritation.

When eyes contact:

Irritation.

When inhalation:

Irritation.

When swallowed:

Small amount may cause considerable health disorders.

Further toxicological information

For more-component products see also the safety-data-sheets of the other components.

12. Ecological information

Additional information

Product is water polluting.

Do not allow to enter waste water drain, waterways or soil.

From current information concerning hazardous substances, environmental effects cannot be claimed at this time.

13. Disposal considerations

Product

Recommendations

Must be disposed of in a special waste disposal unit in accordance with the corresponding regulations.

See chapter 15, national regulations.

Packaging

Recommendations

Completely emptied packagings can be given for recycling.

Packaging that cannot be cleaned should be disposed of as product waste

Product name: **Sikafloor®-91 Part A**

Date of printing: 20.02.2003

Page: 6/7

Revised: 20.02.2003

SDS No.: 090D

14. Transport information

ADG/ADR/RID

UN No.: N/A Class: N/A Packing group: N/A

Proper shipping name

N/A

Label No.: 9

IMO/IMDG

UN No.: 3082 Class: 9 Packing group: III

Proper shipping name

Environmentally hazardous substance, liquid, n.o.s.

contains: Epoxide resin

Label No.: 9

IATA/ICAO

Further information

No dangerous goods.

* 15. Regulatory information

Labelling according to EEC Directive

The product is classified and labelled in accordance with

EC directives/the relevant national laws.

Relevant hazardous ingredients for labelling

Contains: reaction product: bisphenol A-(epichlorhydrin)
epoxy resin (number average molecular weight <= 700)
oxirane, mono[(C12-14-alkyloxy)methyl]derivs.

Danger symbols

Xi Irritant

N Dangerous to environment

R phrases

36/38 Irritating to eyes and skin.

43 May cause sensitization by skin contact.

51/53 Toxic to aquatic organisms, may cause long-term
adverse effects in the aquatic environment.

S phrases

2 Keep out of reach of children

24 Avoid contact with skin.

37 Wear suitable gloves.

Special labelling for certain preparations

Contains epoxy-containing compounds.

Observe manufacturer's instructions.

National regulations

Poisons Schedule (SUSDP) (AUS)

S5 Poison (contains epoxy resins)

Product name: **Sikafloor®-91 Part A**

Date of printing: 20.02.2003

Page: 7/7

Revised: 20.02.2003

SDS No.: 090D

* 15. Regulatory information (continued)

Toxicity class 4 SFOPH T No.: 615084

Water hazardous class (WGK)

WGK 2

Brandklasse (CH)

4

Abfallcode und Abfallbezeichnung (CH)

DISPOSE AS SPECIAL WASTE: PAINT HAVING AN ORGANIC PHASE
(BASIS EPOXY RESIN).

* 16. Other information

Epoxy resins contain residual amounts, typically less than 10 ppm of Epichlorohydrin (CAS No. 106-89-8) as a result of the chemical reaction process in which they are made.

asterisk (*) on left margin marks modification of previous version

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to any use and processing.

Safety Data Sheet

according to 91/155/EEC and ISO 11014-1
(see instructions in Annex to 93/112/EC)

Date of printing: 24.02.2003

Page: 1/7

Revised: 24.02.2003

SDS No. 066C

HAZARDOUS ACCORDING TO THE CRITERIA OF WORKSAFE AUSTRALIA

1. Identification of the substance/preparation and company

Product

Product name

Sikafloor®-91 Part B Normal

Manufacturer/supplier information

Manufacturer/supplier:

Sika Australia Pty Ltd

Street/postbox:

55 Elizabeth Street

Town/City and Post Code:

WETHERILL PARK NSW

Country:

Australia

Phone:

(02) 9725 1145

Telefax:

(02) 9725 3330

Emergency information phone:

1800 033 111

* 2. Composition/information on ingredients

Chemical characterization

Modified polyamine

Hazardous ingredients

Designation according to 67/548/EEC

CAS No.

Concentration

Danger symbols

R phrases

• Benzyl alcohol

100-51-6

30 - 60 %

Xn

20/22/22

• 3-aminomethyl-3,5,5-trimethylcyclohexylamine

2855-13-2

10 - 30 %

C

21/22,34,41,43

• 3,6-diazaoctanethylenediamin

112-24-3

10 - 30 %

C

21,34,43,52/53

• 2,4,6-tris(dimethylaminomethyl)phenol

90-72-2

1 - 10 %

Xi

36/38

* 3. Hazards identification

Hazards identification

C

Corrosive

Information on hazards to man and to the environment

20/21/22

Harmful by inhalation, in contact with skin and if swallowed.

34

Causes burns.

41

Risk of serious damage to eyes.

43

May cause sensitization by skin contact.

52/53

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

* 4. First-aid measures

General instructions

In any case show the physician the Safety Data Sheet

* 4. First-aid measures (continued)

After inhalation

In the event of symptoms take medical treatment.

After skin contact

In case of contact with skin wash off immediately with soap and water

Consult a doctor if skin irritation persists.

After eye contact

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water.

Transport immediately to hospital.

After ingestion

Do not induce vomiting. Rinse mouth with water. Give a glass of water to drink.

Summon a doctor immediately.

5. Fire-fighting measures

Suitable extinguishing media

compatible with all usual extinguishing media

Exposure hazard arising from the product, its combustion products or resulting gases

In the event of fire the following can be released:

Carbon monoxide (CO)

Carbondioxide (CO₂)

Nitrogen oxides (NO_x)

Additional information

Fire residues and contaminated firefighting medium must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

6. Accidental release measures

Personal precautions

Remove persons to safety.

Ensure adequate ventilation.

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

Environmental precautions

In case of entry into waterways, soil or drains, inform the responsible authorities.

Procedures for cleaning up

Pick up with absorbent material.

When picked up, treat material as prescribed under heading "Disposal".

*** 7. Handling and storage**

Handling

Instructions for safe handling
See chapter 8 / Personal protective equipment.

Instructions for fire and explosion protection
Not applicable.

Storage

Classified as combustible liquid - UN00Cl as per AS 1940.

Requirements for storage rooms and containers
Store in accordance with AS 1940.
Keep container tightly closed and dry in a cool, well-ventilated place

Combined storage instructions
Keep away from food, beverages and animal feedstocks.

Additional information regarding storage
Protect from frost.
Protect from heat and direct sunlight
Protect from atmospheric moisture and water

*** 8. Exposure controls/personal protection**

Exposure Standards

100-51-6	None established	Worksafe
2855-13-2	None established	Worksafe
112-24-3	None established	Worksafe
90-72-2	None established	Worksafe

Personal protective equipment

General protective and hygiene measures
Take care for sufficient ventilation or exhaust on the workshop place.
Avoid contact with eyes and skin
Use barrier skin cream.
Remove soiled or soaked clothing immediately.
Do not eat, drink or smoke during work time.
Wash hands before breaks and after work.

Respiratory protection
Not applicable.

Hand protection
Butyl rubber/nitrile rubber gloves

Eye protection
Safety glasses

Body protection
Working clothes

9. Physical and chemical properties

Appearance

Physical state: liquid
Colour: yellow
Odour: of ammonia

Data relevant to safety

		Method
Melting point	-35 °C	
Boiling point	277 °C	
Flash point	122 °C	Pensky Martens
Auto-ignition temperature	335 °C	
Vapour pressure at 20°C	< 0.01 kPa	
Density at 20°C	1.01 g/cm ³	
Solubility in water at 20°C	miscible	
pH value at 20°C (10g/100ml water)	12	
Viscosity at 20°C	30 mPas	

10. Stability and reactivity

Materials to avoid/dangerous reactions

No hazardous reactions when stored and handled according to prescribed instructions.

Thermal decomposition and hazardous decomposition products

No decomposition if used as prescribed.

*** 11. Toxicological information**

Sensitization

Sensitization/allergic reaction possible.

Allergic reaction can may be observed in sensitized persons, even on very low concentrations.

Experience on humans

When skin contact:

Harmful effects.

When eyes contact:

May cause irritation.

Product name: **Sikafloor®-91 Part B Normal**

Date of printing: 24.02.2003

Page: 5/7

Revised: 24.02.2003

SDS No. 066C

11. Toxicological information (continued)

When inhalation:

Harmful effects.

When swallowed:

Small amount may cause considerable health disorders.

12. Ecological information

Additional information

Do not allow to enter waste water drain, waterways or soil.

Due to the high pH, aquatic organisms may be harmed.

From current information concerning hazardous substances, environmental effects cannot be claimed at this time.

13. Disposal considerations

Product

Recommendations

Must be disposed of in a special waste disposal unit in accordance with the corresponding regulations.

See chapter 15, national regulations.

Packaging

Recommendations

Completely emptied packagings can be given for recycling.

Packaging that cannot be cleaned should be disposed of as product waste

14. Transport information

ADG/ADR/RID

UN No.: 1760 Class: 8 Packing group: II

Proper shipping name

Corrosive liquid, N.O.S. *

contains: Triethylenetetramine

Label No.:

IMO/IMDG

UN No.: 1760 Class: 8 Packing group: II

EmS: 8-05

Proper shipping name

Corrosive liquid, N.O.S. *

contains: Triethylenetetramine

Label No.:

Product name: **Sikafloor®-91 Part B Normal**

Date of printing: 24.02.2003

Page: 6/7

Revised: 24.02.2003

SDS No. 066C

14. Transport information (continued)

IATA/ICAO

UN No.: 1760 Class: 8 Packing group: II

Proper shipping name

Corrosive liquid, N.O.S. *

contains: Triethylenetetramine

Label No.: 8

*** 15. Regulatory information**

Labelling according to EEC Directive

The product is classified and labelled in accordance with EC directives/the relevant national laws.

Relevant hazardous ingredients for labelling

Contains: 3,6-diazaoctanethylenediamin

Danger symbols

C Corrosive

R phrases

20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

34 Causes burns.

41 Risk of serious damage to eyes

43 May cause sensitization by skin contact.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S phrases

2 Keep out of reach of children

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

National regulations

Poisons Schedule (SUSDP) (AUS)

S5 Poison (contains > 20 % amines)

Toxicity law (CH)

Toxicity class 3 SFOPH T No.: 617363

Water hazardous class (WGK)

WGK 2

Brandklasse (CH)

4

Abfallcode und Abfallbezeichnung (CH)

DISPOSE AS SPECIAL WASTE: PAINT HAVING AN ORGANIC PHASE (BASIS AMINE).

Product name: **Sikafloor®-91 Part B Normal**

Date of printing: 24.02.2003

Page: 7/7

Revised: 24.02.2003

SDS No. 066C

* 15. Regulatory information (continued)

Weitere Hinweise

Unfallmerkblatt Sika CH: 8

16. Other information

asterisk (*) on left margin marks modification of previous version

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to any use and processing.



Safety Data Sheet

According to NOHSC:2011(2003)

Version: 1.0
Revised: 06 March 2007

Page: 1 of 5
MSDS No: 4B

CLASSIFIED AS HAZARDOUS ACCORDING TO NOHSC CRITERIA

1. Identification of the substance/preparation and company

Product:

Sikafloor – 91 Rapid Part B

Recommended use:

Hardener for Sikafloor 91 Rapid.

Manufacturer/supplier information:

Manufacturer/supplier:	Sika Australia Pty Ltd
Street/postbox:	55 Elizabeth Street
Town/city and Post Code:	WETHERILL PARK NSW 2164
Country:	AUSTRALIA
Phone:	(02) 9725 1145
Fax:	(02) 9725 3330
General information	Operations Manager

Emergency information phone: 1800 033 111

2. Composition/information on ingredients

Chemical characterization:

Solvent free liquid

Hazardous ingredients:

Ingredient	CAS No	Concentration
TMD	25620-58-0	10-30%
Cycloaliphatic amine		>60%
Para toluene sulphonic acid	104-15-4	1-10%

3. Hazard identification

Hazard Category:

C Corrosive

Risk Phrase(s):

R20/22:	Harmful by inhalation and if swallowed.
R34:	Causes burns.
R43:	May cause sensitisation by skin contact.

Safety Phrase(s):

S24/25:	Avoid contact with skin and eyes.
S36/37/39:	Wear suitable protective clothing, gloves and eye/face protection.

4. First-aid measures

Inhalation:

Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice. Seek medical advice if effects persist.

Skin contact:

For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.



Safety Data Sheet

According to NOHSC:2011(2003)

Version: 1.0

Page: 2 of 5

Revised: 06 March 2007

MSDS No: 4B

Eye contact:

Immediately irrigate with copious quantities of water for 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport to hospital or medical centre.

Ingestion:

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766). Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Get to a doctor or hospital quickly.

Notes to physician:

Treat symptomatically. Effects may be delayed. Can cause corneal burns.

5. Fire-fighting measures

Specific hazards:

Combustion will release oxides of carbon and nitrogen.

Special protective precautions and equipment:

On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Suitable extinguishing media:

If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

6. Accidental release measures

Small Spills:

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

Large spills:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

7. Handling and storage

Handling:

Avoid skin and eye contact and inhalation of vapour.

Storage:

Store in a cool, dry, well-ventilated place and out of direct sunlight.
Keep away from foodstuffs.
Keep containers closed when not in use - check regularly for leaks.

8. Exposure controls/personal protection

National occupational exposure limits:

No value assigned for this specific material by the NOHSC Australia.



Safety Data Sheet

According to NOHSC:2011(2003)

Version: 1.0

Page: 3 of 5

Revised: 06 March 2007

MSDS No: 4B

Biological Limit Values:

As per the "National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC: 1005 (1994)]" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures:

Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use with local exhaust ventilation or while wearing appropriate respirator. Keep containers closed when not in use.

Personal protection equipment:

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.

Wear overalls, chemical goggles and impervious gloves. Due to variations in glove construction and local conditions, the user should make an assessment of the appropriate gloves to use. Wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using. If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. Physical and chemical properties

Appearance:

Physical state: liquid
Colour: Straw colour
Odour: Amine odour

Data relevant to safety:

Solubility:	Partly soluble in water.
Specific Gravity (20 °C):	1.02
Vapour Pressure (20 °C):	N Av
Flash Point (°C):	121
Flammability Limits (%):	N Av
pH:	N App
Viscosity (20 °C):	400 mPa.s

(Typical values only - consult specification sheet)

N Av = Not available

N App = Not applicable

10. Stability and reactivity

Chemical stability:

This material is thermally stable when stored and used as directed.

Conditions to avoid:

Elevated temperatures and sources of ignition.

Incompatible Materials:

Oxidising agents, acids and alkalis.

Hazardous decomposition products:

Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions:

No information available.



Safety Data Sheet

According to NOHSC:2011(2003)

Version: 1.0
Revised: 06 March 2007

Page: 4 of 5
MSDS No: 4B

11. Toxicological information

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects:

Inhalation: Harmful by inhalation. Material may be irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns. A skin sensitizer. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Eye contact: A severe eye irritant. Corrosive to eyes: contact can cause corneal burns. Contamination of eyes can result in permanent injury.

Ingestion: Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.

Long Term Effects:

No information available for product.

Acute toxicity / Chronic toxicity:

No LD50 data available for the product.

12. Ecological information

Avoid contaminating waterways.

Ecotoxicity:

No information available.

Persistence and degradability:

No information available.

Mobility:

Partially soluble in water.

13. Disposal considerations

Refer to State/Territory Land Waste Management Authority.

14. Transport information

ADG/ADR/RID

UN No:	2735
Dangerous Goods Class:	8
Packing Group:	III
Hazchem Code:	2R
Emergency Response Guide No:	37

Proper Shipping Name: CORROSIVE LIQUID, N.O.S. (contains CYCLOALIPHATIC AMINE)

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), dangerous when wet substances (Class 4.3), oxidising agents (Class 5.1), organic peroxides (Class 5.2), cyanides of Class 6, radioactive substances (Class 7) or food and food packaging in any quantity, however exemptions may apply. Note that material is incompatible with acids and alkalis.



Safety Data Sheet

According to NOHSC:2011(2003)

Version: 1.0

Page: 5 of 4

Revised: 06 March 2007

MSDS No: 4B

IMDG

UN No: 2735
Dangerous Goods Class: 8
Packing Group: III

Proper Shipping Name: CORROSIVE LIQUID, N.O.S. (contains CYCLOALIPHATIC AMINE)

IATA

UN No: 2735
Dangerous Goods Class: 8
Packing Group: III

Proper Shipping Name: CORROSIVE LIQUID, N.O.S. (contains CYCLOALIPHATIC AMINE)

15. Regulatory information

Poisons Schedule (Aust):

This material is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. Other information

Reason(s) For Issue: Revised

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy. MSDS may be obtained from the following website: www.sika.com.au

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to any use and processing.